

LD-12 PROFESSIONAL'S WATER LEAK DETECTOR





Standard Items

- Amplifier with Meter Display and Filter Controls
- (2) Ground Microphone and Handswitch
- (3) Aviation-Grade Stereo Headphones
- Heavy-Duty ABS Plastic Carrying Case

Features

- Large meter display (with backlight) of sound loudness, allowing the user to pinpoint the exact leak location.
- · Light weight amplifier, weighing only 31 ounces, with a padded carrying case and a strap.
- · Six selectable filters, split into three "low side" filters (100Hz, 200Hz, or 400Hz) and three "high side" filters (600Hz, 800Hz, or 1200Hz).





- · High-sensitivity ground microphone and low "electronic noise" amplifier combine to offer the very best quality sound for leak detection.
- Three accessories for attachment to the sensor:
 - · Ground plate for pinpointing on streets/slabs
 - · Magnet base for surveying at hydrants/valves
 - Contact rod for surveying at meters/fittings

Standard Accessories

- (5) Magnet Base
- 6 3-Section Contact Rod
- Nut Driver (to remove base)
- (8) Instruction Manual (not shown)

Specifications

Amplifier

 Input Impedance : 50k ohms Output Impedance : 15 ohms Amplification : 62 dB +/- 3dB · Frequency Range : 1)100Hz to 1200Hz

(13 dB) with Filter-Thru OFF 2) 15Hz to 30,000Hz

(13 dB) with Filter-Thru ON

 Power : 6 AA dry cell batteries Power Consumption : 1)70 mA or less with backlight ON

2)35 mA or less with backlight OFF Battery Life : 1)28 hours with backlight OFF

(alkaline cells) 2) 14 hours with backlight ON

(alkaline cells) · Weight : 31 ounces (885 g) : 6.7" x 2.8" x 4.1' Size

(17.0cm x 7.1cm x 10.3cm)

ABS Carrying Case

Weight (full)

: 16.4 lb. (7.43 Kg) Size : 18.5" x 14.6" x 7.5"

(470mm x 371mm x 190mm)

Distributed by:



1841-C Plane Park Drive De Pere, WI 54115 USA www.ssilocators.com

(855) 422-6346 toll free (920) 347-1791 fax info@ssilocators.com

Scan the QR code for videos, photos, and more information.

