

Distributed by SubSurface Instruments, Inc.



**SUBSURFACE
INSTRUMENTS, INC**

MODEL LD-18 DIGITAL WATER LEAK DETECTOR

With digital noise reduction that removes intermittent sounds like barking dogs and passing vehicles!

**855-422-6346 toll free
www.ssilocators.com**



Graph the leak sound levels at 5-10 spots directly over the pipe. Let the LD-18's amplifier pinpoint the leak's location for you instead of relying upon your hearing.

LD-18 DIGITAL WATER LEAK DETECTOR



Standard Items

- ① Amplifier with LCD Display, Controls, and USB Connection (to PC Computers)
- ② Padded Case for Amplifier
- ③ 40 inches Belt (50 inches and 60 inches Optional)
- ④ Ground Microphone and Handswitch
- ⑤ Magnet Base and Nutdriver

Features

All-digital amplifier with automatic noise reduction of intermittent sounds, high and low filters, storage and graphing of sound levels at different locations on the pipe, bar graph and numeric display of sound loudness, USB connection, and back light.



LD-18 Amplifier showing filter settings, bar graph and numeric display of sound loudness, and minimum sound level detected

Automatic noise reduction capability for intermittent noises such as pedestrian footsteps, people talking, and passing vehicles.

5 High Frequency filters, 3 Low Frequency filters (plus Low filter OFF), and 2 Notch filters (plus Notch filter OFF) to remove continuous interfering noises from A/C hum, motors, wind, etc.

Storage and graphical display of the leak's loudness at multiple locations along the pipe.



The "Saved" data file showing 10 leak sound levels and graphical display. Leak is at the peak sound level in the center.

Standard Accessories

- ⑥ Heavy-Duty ABS Plastic Carrying Case
- ⑦ Aviation-Grade Stereo Headphones
- ⑧ PC Software and USB Cable

Optional Accessories

- ⑨ Sensor with Strong Magnet and 9.75 ft. Cable (to listen at valves and hydrants)

Specifications

Amplifier

- Combined Sensitivity : 900 V/G or higher (at 400 Hz) and Amplification
- Low Filters : Off, 100 Hz, 200 Hz, 400 Hz
- High Filters : 400 Hz, 600 Hz, 800 Hz, 1200 Hz, 2200 Hz
- Notch Filters : Off, 50 Hz, 60 Hz
- Maximum No. of Sound Levels Saved in File : 250 (by date and time)
- Power : 4 C dry cell batteries
- Battery Life (continuous use) : 24 hours minimum
- Frequency Range : 50 Hz to 2200 Hz
- Weight : 35 ounces (including 4 C batteries)
- Size : 6.4" x 3.0" x 5.7" (163mm x 76mm x 145mm)
- Weather Resistance : IP52 equivalent
- Temperature Range (Working) : Minus 4 F to Positive 130 F

Sensor

- Type : Piezo electric ceramic
- Weather Resistance : IP67 equivalent (3 ft water depth for 30 minutes)
- Standard Base : 3 - Pronged Plate (removable with nutdriver)

Distributed by:



1841-C Plane Park Drive
De Pere, WI 54115 USA
www.ssilocators.com

(855) 422-6346 toll free
(920) 347-1791 fax
info@ssilocators.com

Scan the QR code
for videos, photos,
and more information.

